



HD2(TM)

Imperial	7'6"	8'	8'6"	9'
Moldboard Options	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel
Blade Type	Straight Blade	Straight Blade	Straight Blade	Straight Blade
Vehicle Compatibility	Truck Class 2 & 3, Skid-Steers & Tractors	Truck Class 2 & 3, Skid-Steers & Tractors	Truck Class 2 & 3, Skid-Steers & Tractors	Truck Class 2 & 3, Skid-Steers & Tractors
Approx. Weight* (Without Mount)	709 lbs	752 lbs	769 lbs	789 lbs
Plowing Width (Full Angle)	6'9"	7'2"	7'7"	8'1"
Blade Width	7'6"	8'	8'6"	9'
Blade Height	29"	29"	29"	29"
Blade Thickness	12 ga	12 ga	12 ga	12 ga
Trip Springs	3	4	4	4
Ribs	10	10	10	10
Lift Cylinder	1½" x 10"	1½" x 10"	1½" x 10"	1½" x 10"
Angling Rams	1½" x 12"	1½" x 12"	1½" x 12"	1½" x 12"
Cutting Edge	3/8 " x 6" Steel (Standard)	½" x 6" Steel (Standard)	½" x 6" Steel (Standard)	½" x 6" Steel (Standard)
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2

Metric	7'6"	8'	8'6"	9'
Models	7'6"	8'	8'6"	9'
Moldboard Options	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel
Blade Type	Straight Blade	Straight Blade	Straight Blade	Straight Blade
Vehicle Compatibility	Truck Class 2 & 3, Skid-Steers & Tractors	Truck Class 2 & 3, Skid-Steers & Tractors	Truck Class 2 & 3, Skid-Steers & Tractors	Truck Class 2 & 3, Skid-Steers & Tractors
Approx. Weight* (Without Mount)	321 kg	341 kg	348 kg	357 kg
Plowing Width (Full Angle)	2.05 m	2.19 m	2.32 m	2.46 m
Blade Width	2.29 m	2.44 m	2.59 m	2.74 m
Blade Height	73.66 cm	73.66 cm	73.66 cm	73.66 cm
Blade Thickness	12 ga	12 ga	12 ga	12 ga
Trip Springs	3	4	4	4
Ribs	10	10	10	10
Lift Cylinder	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm
Angling Rams	3.81 cm x 30.48 cm	3.81 cm x 30.48 cm	3.81 cm x 30.48 cm	3.81 cm x 30.48 cm
Cutting Edge	0.95 cm x 15.24 cm (Standard)	1.27 cm x 15.24 cm (Standard)	1.27 cm x 15.24 cm (Standard)	1.27 cm x 15.24 cm (Standard)
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2

* Does not include vehicle mount (approx. 60 lbs - 184 lbs for straight blades). Please refer to the eMatch program for specific vehicle applications.