



XtremeV™ Specifications

Specifications

Imperial	7' 6" SS	8' 6" PC or SS	9' 6" PC or SS
Blade Width	7' 6"	8' 6"	9' 6"
Blade Height	30 ¾" at end 29" at hinge	31" at end 29" at hinge	33" at end 31" at hinge
Blade Gauge	14	14	14
Trip Springs	4	4	6
Ribs	12	12	12
Lift Cylinder	1½" x 10"	1½" x 10"	1½" x 10"
Angling Rams	1¾" x 11"	1¾" x 11"	1¾" x 11"
Plowing Width (full angle)	6' 6" full angle 6' 3" scoop 6' 9" full V	7' 5" full angle 7' 1" scoop 7' 7" full V	8' 3" full angle 7' 11" scoop 8' 7" full V
Approx. Weight*	821 lb	899 lb	1013 lb
Wear Shoes	Optional	Optional	Optional
Cutting Edge	3/8" x 6" 1/2" x 6"***	3/8" x 6" 1/2" x 6"***	1/2" x 6"
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2

Metric	7' 6" SS	8' 6" PC or SS	9' 6" PC or SS
Blade Width	2.29 m	2.59 m	2.90 m
Blade Height	78.11 cm at end 73.66 cm at hinge	78.74 cm at end 73.66 cm at hinge	83.82 cm at end 78.74 cm at hinge
Blade Gauge	2.66 mm	2.66 mm	2.66 mm
Trip Springs	4	4	6
Ribs	12	12	12
Lift Cylinder	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm
Angling Rams	4.44 cm x 27.94 cm	4.44 cm x 27.94 cm	4.44 cm x 27.94 cm
Plowing Width (full angle)	1.98 m full angle 1.91 m scoop 2.06 m full V	2.26 m full angle 2.16 m scoop 2.31 m full V	2.51 m full angle 2.41 m scoop 2.62 m full V
Approx. Weight*	372 kg	407 kg	459 kg
Wear Shoes	Optional	Optional	Optional
Cutting Edge	0.95 cm x 15.24 cm 1.27 cm x 15.24 cm**	0.95 cm x 15.24 cm 1.27 cm x 15.24 cm**	1.27 cm x 15.24 cm
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2