



# XV2™ Specifications

## Specifications

Imperial	7' 6" SS	8' 6" PC or SS	9' 6" PC or SS
Blade Width	7' 6"	8' 6"	9' 6"
Blade Height	37" at end 31" at hinge	38" at end 31" at hinge	39" at end  31" at hinge
Blade Gauge	14	14	14
Trip Springs	4	4	6
Ribs	12	12	12
Lift Cylinder	1¾" x 10"	1¾" x 10"	1¾" x 10"
Angling Rams	1¾" x 11"	1¾" x 11"	1¾" x 11"
Plowing Width (full angle)	6' 7" full angle 6' 4" scoop 6' 10" full V	7' 5" full angle  7' 2" scoop 7' 8" full V	8' 6" full angle  8' 2" scoop  8' 7" full V
Approx. Weight*	914 lb	957 lb	1044 lb
Wear Shoes	Optional	Optional	Optional
Cutting Edge	3/8" x 6" 1/2" x 6"***	3/8" x 6" 1/2" x 6"***	1/2" x 6"
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2

Metric	7' 6" SS	8' 6" PC or SS	9' 6" PC or SS
Blade Width	2.29 m	2.59 m	2.90 m
Blade Height	93.98 cm at end 78.74 cm at hinge	96.52 cm at end 78.74 cm at hinge	99.06 cm at end 78.74 cm at hinge
Blade Gauge	1.98 mm	1.98 mm	1.98 mm
Trip Springs	4	4	6
Ribs	12	12	12
Lift Cylinder	4.44 cm x 25.40 cm	4.44 cm x 25.40 cm	4.44 cm x 25.40 cm
Angling Rams	4.44 cm x 27.94 cm	4.44 cm x 27.94 cm	4.44 cm x 27.94 cm
Plowing Width (full angle)	2.01 m full angle 1.93 m scoop 2.08 m full V	2.26 m full angle 2.18 m scoop 2.34 m full V	2.59 m full angle 2.49 m scoop 2.62 m full V
Approx. Weight*	414 kg	434 kg	473 kg
Wear Shoes	Optional	Optional	Optional
Cutting Edge	0.95 cm x 15.24 cm 1.27 cm x 15.24 cm**	0.95 cm x 15.24 cm 1.27 cm x 15.24 cm**	1.27 cm x 15.24 cm
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2