



# XLS™ Specifications

## Specifications

Imperial	8'-10' (180209-lower)	8'-10' (180210-higher)	8' 6"-11'
Blade Width	8' retracted 10' expanded 8' 10" scoop	8' retracted 10' expanded 8' 10" scoop	8' 6" retracted 11' expanded 9' 10" scoop
Blade Height	29"	31" on moldboard 35" at end	31" on moldboard 36" at end
Blade Gauge	12	14	14
Trip Springs	4	4	4
Vertical Ribs	10	10	10
Angling Rams	1½" x 10"	1½" x 10"	1½" x 10"
Lift Cylinder	1½" x 10"	1¾" x 10"	1¾" x 10"
Plowing Width (full angle)	7' 2" retracted 9' expanded 7' 11" scoop	7' 2" retracted 9' expanded 7' 11" scoop	7' 11" retracted 10' 6" expanded 9' 6" scoop
Approx. Weight*	985 lb	1107 lb	1140 lb
Wear Shoes	Optional	Optional	Optional
Blade Cutting Edge	Optional	1/2" x 6" steel	1/2" x 6" steel
Wing Cutting Edge	1½" x 9" polyurethane	1½" x 9" polyurethane	1½" x 9" polyurethane
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2

Metric	8'-10' (180209-lower)	8'-10' (180210-higher)	8' 6"-11'
Blade Width	2.44 m retracted 3.05 m extended 2.69 m scoop	2.44 m retracted 3.05 m extended 2.69 m scoop	2.59 m retracted 3.35 m extended 3 m scoop
Blade Height	73.66 cm	78.74 cm on moldboard 88.9 cm at end	78.74 cm on moldboard 91.44 cm at end
Blade Gauge	2.66 mm	2.1 mm	2.1 mm
Trip Springs	4	4	4
Vertical Ribs	10	10	10
Angling Rams	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm
Lift Cylinder	3.81 cm x 25.40 cm	4.45 cm x 25.40 cm	4.45 cm x 25.40 cm
Plowing Width (full angle)	2.18 m retracted 2.74 m expanded 2.41 m scoop	2.18 m retracted 2.74 m expanded 2.41 m scoop	2.41 m retracted 3.20 m expanded 2.90 m scoop
Approx. Weight*	446.79 kg	502.13 kg	517.10 kg
Wear Shoes	Optional	Optional	Optional
Blade Cutting Edge	Optional	1.27 cm x 15.24 cm steel	1.27 cm x 15.24 cm steel
Wing Cutting Edge	3.81 cm x 22.86 cm polyurethane	3.81 cm x 22.86 cm polyurethane	3.81 cm x 22.86 cm polyurethane
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2