



XV2™ Specifications

Specifications

Imperial	7' 6" SS	8' 6" PC or SS	9' 6" PC or SS
Blade Width	7' 6"	8' 6"	9' 6"
Blade Height	31" at center 37" at end	31" at center 38" at end	31" at center 39" at end
Blade Gauge	14	14	14
Trip Springs	4	4	6
Ribs	12	12	12
Lift Cylinder	1¾" x 10"	1¾" x 10"	1¾" x 10"
Angling Rams	1¾" x 11"	1¾" x 11"	1¾" x 11"
Plowing Width (full angle)	6' 7" full angle scoop 6' 10" full V	7' 5" full angle 7' 2" scoop 7' 8" full V	8' 6" full angle 8' 2" scoop 8' 7" full V
Approx. Weight*	914 lb	957 lb	1044 lb
Wear Shoes	Optional	Optional	Optional
Cutting Edge	3/8" x 6" 1/2" x 6"***	3/8" x 6" 1/2" x 6"***	1/2" x 6"
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2

Metric	7' 6" SS	8' 6" PC or SS	9' 6" PC or SS
Blade Width	2.29 m	2.59 m	2.90 m
Blade Height	78.74 cm at center 93.98 cm at end	78.74 cm at center 96.52 cm at end	78.74 cm at center 99.06 cm at end
Blade Gauge	1.98 mm	1.98 mm	1.98 mm
Trip Springs	4	4	6
Ribs	12	12	12
Lift Cylinder	4.44 cm x 25.40 cm	4.44 cm x 25.40 cm	4.44 cm x 25.40 cm
Angling Rams	4.44 cm x 27.94 cm	4.44 cm x 27.94 cm	4.44 cm x 27.94 cm
Plowing Width (full angle)	2.01 m full angle 1.93 m scoop 2.08 m full V	2.26 m full angle 2.18 m scoop 2.34 m full V	2.59 m full angle 2.49 m scoop 2.62 m full V
Approx. Weight*	414 kg	434 kg	473 kg
Wear Shoes	Optional	Optional	Optional
Cutting Edge	0.95 cm x 15.24 cm 1.27 cm x 15.24 cm**	0.95 cm x 15.24 cm 1.27 cm x 15.24 cm**	1.27 cm x 15.24 cm
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2