



EZ-V® Specifications

Technical Specifications

Imperial	7' 6" SS	7' 6" PC
Blade Width	7' 6"	7' 6"
Blade Height	27" at Center 33" at End	27" at Center 33" at End
Blade Gauge	14 ga	14 ga
Trip Springs	2	2
Ribs	6 Vertical 2 Horizontal	6 Vertical
Lift Cylinder	1 1/4" x 8 5/8"	1 1/4" x 8 5/8"
Angling Rams	1 1/2" x 12"	1 1/2" x 12"
Plowing Width	6' 7" Full Angle 6' 5" Scoop 6' 9" Full V	6' 7" Full Angle 6' 5" Scoop 6' 9" Full V
Approx. Weight*	553 lb	508 lb
Cutting Edge	3/8" x 6"	3/8" x 6"
Mount Type	Minute Mount® 2	Minute Mount® 2

Metric	7' 6" SS	7' 6" PC
Blade Width	2.29 m	2.29 m
Blade Height	68.58 cm at Center 83.82 cm at End	68.58 cm at Center 83.82 cm at End
Blade Gauge	1.98 mm	1.98 mm
Trip Springs	2	2
Ribs	6 Vertical 2 Horizontal	6 Vertical
Lift Cylinder	3.18 cm x 21.91 cm	3.18 cm x 21.91 cm
Angling Rams	3.81 cm x 30.48 cm	3.81 cm x 30.48 cm
Plowing Width	2.01 m Full Angle 1.96 m Scoop 2.06 m Full V	2.01 m Full Angle 1.96 m Scoop 2.06 m Full V
Approx. Weight*	250.84 kg	230.43 kg
Cutting Edge	0.95 cm x 15.24 cm	0.95 cm x 15.24 cm
Mount Type	Minute Mount® 2	Minute Mount® 2