



SPEED-CASTER(TM) 525 & 900 Specifications

Technical Specifications

| Imperial | SPEED-CASTER 525 | SPEED-CASTER 900 |
|----------------------------|--|---|
| Capacity | 5.25 cu ft | 9.00 cu ft |
| Hopper Construction | Polyethylene | Polyethylene |
| Dimensions Overall (LxWxH) | 20 1/2" x 38" x 34" | 24" x 52" x 36" |
| Approx. Weight (Empty) | 160 lb | 180 lb |
| Motor | Dual Electric, 12V 1/3 HP | Dual Electric, 12V 1/3 HP |
| Auger (Diam. x Length) | 3" x 14" Heavy-Duty Solid Steel | 3" x 20" Heavy-Duty Solid Steel |
| Spinner Size | 10" | 12" |
| Spreading Width | Up to 30' | Up to 40' |
| Materials | Bagged Rock Salt | Bagged Rock Salt |
| Vehicle Application | Tractors, UTVs, SUVs, 1-Ton or Smaller Pickups | Tractors, 1-Ton or Smaller Pickups |
| Available Mounts | Standard 2" Receiver, 3-Point Combo Mount | Pivot Mount, 2" Receiver Mount (Requires Adapter Mount), 3-Point Hitch Mount* |

| Metric | SPEED-CASTER 525 | SPEED-CASTER 900 |
|----------------------------|--|---|
| Capacity | 0.15 cu m | 0.25 cu m |
| Hopper Construction | Polyethylene | Polyethylene |
| Dimensions Overall (LxWxH) | 52.10 cm x 96.50 cm x 86.40 cm | 60.90 cm x 132.10 cm x 91.40 cm |
| Approx. Weight (Empty) | 72.6 kg | 81.7 kg |
| Motor | Dual Electric, 12V 1/3 HP | Dual Electric, 12V 1/3 HP |
| Auger (Diam. x Length) | 7.62 cm x 35.56 cm Heavy-Duty Solid Steel | 7.62 cm x 50.80 cm Heavy-Duty Solid Steel |
| Spinner Size | 25.40 cm | 30.50 cm |
| Spreading Width | Up to 9.14 m | Up to 12.19 m |
| Materials | Bagged Rock Salt | Bagged Rock Salt |
| Vehicle Application | Tractors, UTVs, SUVs, 1-Ton or Smaller Pickups | Tractors, 1-Ton or Smaller Pickups |
| Available Mounts | Standard 2" Receiver, 3-Point Combo Mount | Pivot Mount, 2" Receiver Mount (Requires Adapter Mount), 3-Point Hitch Mount* |