



XLS(TM) Specifications

Technical Specifications

Imperial	8'-10' (180209-lower)	8'-10' (180210-higher)	8' 6"-11'
Blade Width	8' Retracted 10' Expanded 8' 10" Scoop	8' Retracted 10' Expanded 8' 10" Scoop	8' 6" Retracted 11' Expanded 9' 10" Scoop
Blade Height	29"	31" at Center 35" at End	31" at Center 36" at End
Blade Gauge	12	14	14
Trip Springs	4	4	4
Vertical Ribs	10	10	10
Lift Cylinder	1 1/2" x 10"	1 3/4" x 10"	1 3/4" x 10"
Angling Rams	1 1/2" x 10"	1 1/2" x 10"	1 1/2" x 10"
Plowing Width	7' 2" Retracted 9' Expanded 7' 11" Scoop	7' 2" Retracted 9' Expanded 7' 11" Scoop	7' 11" Retracted 10' 6" Expanded 9' 6" Scoop
Approx. Weight*	985 lb	1,107 lb	1,140 lb
Blade Cutting Edge	Optional	1/2" x 6" Steel	1/2" x 6" Steel
Wing Cutting Edge	1 1/2" x 9" Polyurethane	1 1/2" x 9" Polyurethane	1 1/2" x 9" Polyurethane
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2

Metric	8'-10' (180209-lower)	8'-10' (180210-higher)	8' 6"-11'
Blade Width	2.44 m Retracted 3.05 m Extended 2.69 m Scoop	2.44 m Retracted 3.05 m Extended 2.69 m Scoop	2.59 m Retracted 3.35 m Extended 3 m Scoop
Blade Height	73.66 cm	78.74 cm at Center 88.9 cm at End	78.74 cm at Center 91.44 cm at End
Blade Gauge	2.66 mm	2.1 mm	2.1 mm
Trip Springs	4	4	4
Vertical Ribs	10	10	10
Lift Cylinder	3.81 cm x 25.40 cm	4.45 cm x 25.40 cm	4.45 cm x 25.40 cm
Angling Rams	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm
Plowing Width	2.18 m Retracted 2.74 m Expanded 2.41 m Scoop	2.18 m Retracted 2.74 m Expanded 2.41 m Scoop	2.41 m Retracted 3.20 m Expanded 2.90 m Scoop
Approx. Weight*	446.79 kg	502.13 kg	517.10 kg
Blade Cutting Edge	Optional	1.27 cm x 15.24 cm Steel	1.27 cm x 15.24 cm Steel
Wing Cutting Edge	3.81 cm x 22.86 cm Polyurethane	3.81 cm x 22.86 cm Polyurethane	3.81 cm x 22.86 cm Polyurethane
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2