



## XV2(TM) Specifications

### Technical Specifications

Imperial	7' 6" SS	8' 6" PC or SS	9' 6" PC or SS	10' 6" PC or SS
Blade Width	7' 6"	8' 6"	9' 6"	10' 6"
Blade Height	31" at Center 37" at End	31" at Center 38" at End	31" at Center 39" at End	35" at Center 45" at End
Blade Gauge	14	14	14	11 PC 12 SS
Trip Springs	4	4	6	6
Ribs	12	12	12	12
Lift Cylinder	1 3/4" x 10"	1 3/4" x 10"	1 3/4" x 10"	1 3/4" x 10"
Angling Rams	1 3/4" x 11"	1 3/4" x 11"	1 3/4" x 11"	2" x 11"
Plowing Width	6' 7" Full Angle 6' 4" Scoop 6' 10" Full V	7' 5" Full Angle 7' 2" Scoop 7' 8" Full V	8' 6" Full Angle 8' 2" Scoop 8' 7" Full V	9' 9" Full Angle 9' 7" Scoop 9' 11" Full V
Approx. Weight*	914 lb	957 lb	1,044 lb	1,222 lb
Cutting Edge	3/8" x 6" 1/2" x 6"***	3/8" x 6" 1/2" x 6"***	1/2" x 6"	1/2" x 6"
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2

Metric	7' 6" SS	8' 6" PC or SS	9' 6" PC or SS	10' 6" PC or SS
Blade Width	2.29 m	2.59 m	2.90 m	3.20 m
Blade Height	78.74 cm at Center 93.98 cm at End	78.74 cm at Center 96.52 cm at End	78.74 cm at Center 99.06 cm at End	88.90 cm at Center 114.30 cm at End
Blade Gauge	1.98 mm	1.98 mm	1.98 mm	3.05 mm PC 2.66 mm SS
Trip Springs	4	4	6	6
Ribs	12	12	12	12
Lift Cylinder	4.44 cm x 25.40 cm	4.44 cm x 25.40 cm	4.44 cm x 25.40 cm	4.44 cm x 25.40 cm
Angling Rams	4.44 cm x 27.94 cm	4.44 cm x 27.94 cm	4.44 cm x 27.94 cm	5.08 cm x 27.94 cm
Plowing Width	2.01 m Full Angle 1.93 m Scoop 2.08 m Full V	2.26 m Full Angle 2.18 m Scoop 2.34 m Full V	2.59 m Full Angle 2.49 m Scoop 2.62 m Full V	2.97 m Full Angle 2.92 m Scoop 3.02 m Full V
Approx. Weight*	414 kg	434 kg	473 kg	554 kg
Cutting Edge	0.95 cm x 15.24 cm 1.27 cm x 15.24 cm**	0.95 cm x 15.24 cm 1.27 cm x 15.24 cm**	1.27 cm x 15.24 cm	1.27 cm x 15.24 cm
Mount Type	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2	Minute Mount® 2