



## XtremeV(TM)

<b>Imperial</b>	<b>8'6"</b>	<b>9'6"</b>
Moldboard Options	Stainless or Powder-Coated Steel	Stainless or Powder-Coated Steel
Blade Type	V-Plow	V-Plow
Vehicle Compatibility	Truck Class 2-3 & Tractors	Truck Class 2-3 & Tractors
Approx. Weight* (Without Mount)	876 lbs	984 lbs
Plowing Width (Full Angle)	Full Angle: 7'5" Scoop: 7'1" Full V: 7'7"	Full Angle: 8'3" Scoop: 7'11" Full V: 8'7"
Blade Width	8'6"	9'6"
Blade Height	At Center: 29" At End: 31"	At Center: 31" At End: 33"
Blade Gauge	14 ga	14 ga
Trip Springs	4	6
Ribs	12	12
Lift Cylinder	1½" x 10"	1½" x 10"
Angling Rams	1¾" x 11"	1¾" x 11"
Cutting Edge	3/8" x 6" (Standard)	½" x 6" (Standard)
Mount Type	Minute Mount® 2	Minute Mount® 2

<b>Metric</b>	<b>8'6"</b>	<b>9'6"</b>
Models	8'6"	9'6"
Moldboard Options	Stainless or Powder-Coated Steel	Stainless or Powder-Coated Steel
Blade Type	V-Plow	V-Plow
Vehicle Compatibility	Truck Class 2-3 & Tractors	Truck Class 2-3 & Tractors
Approx. Weight* (Without Mount)	397 kg	446 kg
Plowing Width (Full Angle)	Full Angle: 2.26 m Scoop: 2.16 m Full V: 2.31 m	Full Angle: 2.51 m Scoop: 2.41 m Full V: 2.62 m
Blade Width	2.59 m	2.90 m
Blade Height	At Center: 73.66 cm At End: 78.74 cm	At Center: 78.74 cm At End: 83.82 cm
Blade Gauge	2.66 mm	2.66 mm
Trip Springs	4	6
Ribs	12	12
Lift Cylinder	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm
Angling Rams	4.45 cm x 27.94 cm	4.45 cm x 27.94 cm
Cutting Edge	0.95 cm x 15.24 cm (Standard)	1.27 cm x 15.24 cm (Standard)
Mount Type	Minute Mount® 2	Minute Mount® 2

\* Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to the eMatch program for specific vehicle applications.